

## CDV4791 Kit

The 2EASY kits from CDVI offer convenient and high quality audio entry.

Connection throughout is 2-wire, non polarised, so installation and maintenance is simple and straightforward.

Robust door stations with stylish handsets - it all adds up to a sophisticated and flexible audio entry system.



### Overview

- Black or white monitor
- Simple, stylish door station
- 2-wire connection
- Expandable
- Compatible with 2Easy video system



The 2EASY system from CDVI offer convenient and high quality video entry. Connection throughout is 2-wire, non polarised providing simple and efficient installation and maintenance.

## CDV47 - Technical Specifications



### Wiring

2 wires, non-polarised

### Video

Monitor screen: 7 inch digital colour TFT  
Video signal: 1Vp-p, 75Ω, CCIR standard  
Display resolutions: 800\*3 (R, G, B) x 480 pixels

### Electrical Specifications

Power input: 12/24 Vdc  
Power supply: 20 to 28 Vdc for indoor monitor

### Dimensions

Dimensions: 131 x 225 x 18mm

## CDV91 - Technical Specifications



### Product Specifications

Material: Zinc alloy panel  
Surface wall-mount  
IP Rating: IP54

### Camera

Colour CMOS, 520TVL  
1/4" camera, 150° wide angle

### Output Specifications

Number of realy circuits: 2\*  
\*the second lock output requires CDV-RLC

### Electrical Specifications

Power Supply: 24Vdc  
Power Consumption: standby 0.8W, working 3W  
Lock Power Supply: 12Vdc, 250mA (Internal power - Fail secure only)


### Wiring

2-wire  
No polarity

### Dimensions

Dimensions: 176 x 90 x 27mm  
Environment: -20°C to 55°C

## CDV-PC6 - Technical Specifications



### Input Specifications

Input voltage: 100-240Vac  
Input frequency: 50-60Hz  
SW port input voltage: max 230Vac, 2A

### Output Specifications

Rated output voltage: 28Vdc + 2Vdc  
Rated output current: 1.5A

### Dimensions

Dimensions: 140 x 90 x 60mm  
Environment: -10°C to 50°C