

## CDV96KP & CDV96KP-SF

The CDV96KP is a standard 1-way door station with an integral keypad.

Part of the 2Easy range, this outdoor station with keypad is available in flush version (CDV96KP-SF - special orders only, contact sales@cdvi.co.uk for more information).

The CDV96KP is compatible with all 2Easy 2-wire system models and is included in all CDV4796KP kits



### Overview

- Stainless steel
- 1-button
- Door panel with integral keypad
- High resolution camera
- 2Easy range compatibility



The 2EASY system from CDVI offer convenient and high quality video entry. Connection throughout is 2-wire, non polarised providing simple and efficient installation and maintenance.

## CDV96KP(-SF) - Technical Specifications

### Product Specifications

Material: Stainless steel panel  
Surface Wall-Mount / Flush mount  
Unlocking time: 1 to 99s

### Camera

Pinhole Sharp Colour CCD, 420TVL

### Output Specifications

Number of realy circuits: 2\*  
\*the second lock output requires CDV-RLC

### Electrical Specifications

Power Supply: 24Vdc  
Power Consumption: standby 60mA, working 200mA  
Lock Power Supply: 12Vdc, 300mA (Internal power - Fail secure only)

### Wiring

2-wire  
No polarity

### Dimensions - CDV96KP

Dimensions: 182 x 93 x 28mm  
Environment: -10°C to 45°C

### Dimensions - CDV96KP-SF

Dimensions: 220 x 120 x 50mm (front panel) - 198 x 95 x 50mm (back box)  
Environment: -10°C to 45°C