

RX26-C

A complete range of radio control and switching products to provide wire-free control of gates, barriers, doors, lights etc. A high quality and a high performance range.

The external receiver range is compatible with all our rolling-code transmitters. The receivers are available in various formats, including low or high voltage input and different relay outputs with combinations of pulse, latched and timed triggers - please consult with CDVI technical for full details.

All external receivers are housed in weather resistant enclosures, and are ideal for the control of external gates, barriers and lighting.

Standard range is up to 200 metres, this can be enhanced by installing the optional SEA433 tuned aerial.



Overview

- External rated receivers
- 1, 2 & 4 channel
- 12-24V ac/dc option
- Relay pulse, timed and latch
- Extension tuned aerial (SEA433)
- Encoding: Keeloq hopping code

RX26-C - Technical Specifications

General Specifications

Demodulation: ASK
 Frequency: 433.92 Mhz
 Encoding: Keeloq hopping code
 Range: 100 to 200 meters in open space
 Dimensions: 140 x 115 x 53mm

Product	Input Voltage	Relays	Relay Contacts	Relays Rating	Relay Options
RX26-C2P	12 or 24V ac/dc	2	1 x N/O, 1 x N/O or N/C	230Vac 3.5kW	PULSE, LATCH OR TIMED
RX26-C4P	12 or 24V ac/dc	4	2 x N/O, 2 x N/O or N/C	230Vac 3.5kW	3 x PULSE ONLY, 1 x PULSE OR LATCH
RX26-C4	12 or 24V ac/dc	4	3 x N/O, 1 x N/O or N/C	24VA	PULSE, LATCH OR TIMED
RX26-V4	230Vac	4	3 x N/O, 1 x N/O or N/C	24VA	PULSE, LATCH OR TIMED
RX26-C2V	230Vac	2	1 x N/O, 1 x N/O or N/C	230Vac 3.5kW	PULSE, LATCH OR TIMED
RX26-C4V	230Vac	4	2 x N/O, 2 x N/O or N/C	230Vac 3.5kW	3 x PULSE ONLY, 1 x PULSE OR LATCH
RX26-C4R	230Vac	4	4 x N/O or N/C	230Vac 3.5kW	PULSE OR LATCH

For more information about the RX26-C receiver range,
 please contact support@cdvi.co.uk