

## RX26-DIN

**The RX26-DIN receiver is ideal for operation of automation and alarm devices requiring up to a maximum contact load of 3.5kW.**

Flexibility comes from 4 full changeover relays along with the option of being able to set pulse or latch for each individual relay.

The RX26-DIN features standard 35mm DIN rail attachment for ease of mounting, 12V AC or DC input supply, external button triggering and connection for the SEA433 antenna (optional).



### Overview

- 12-24V AC/DC Supply
- 3.5kW Contact Rating
- 4 Changeover Relays (NO, Com, NC)
- Selectable Latch (step) or Pulse Output
- 4 Auxiliary Inputs
- LED Relay Operating & Programming
- DIN Rail Mounting
- 85 Transmitter Memory
- Single Transmitter or Full Memory Erasure
- Memorization PLUS
- Rolling Code (Keeloq) @ 433Mhz
- Input for SEA433 External Antenna

## RX26-DIN - Technical Specifications

### Product Specifications

Receiver type: Supereheterodyne  
Memory capacity: 85 transmitters  
Demodulation: AM/ASK  
Carrier frequency: 433.92 MHz  
Local oscillator frequency: 6,6128 MHz  
Intermediate frequency: 10,7 MHz  
Channel width: >25 KHz  
Local oscillator emissions: <-57 dBm  
Sensitivity (for good signal): -115 dBm  
Encoding: Keeloq hopping code  
IP Rating: IP2X

### Electrical Specifications

Input load: 50 Ohm  
Power supply: 12 Vac/dc  
Current consumption: @12Vdc = 120mA - @12Vac = 250mA

### Relays

Number of relays: 4  
Relay contacts: NO/Com/NC  
Max current on relay output: 3.5kW / 230Vac  
Relay operating mode: latched (step) or pulse

### Dimensions

Dimensions: 70 x 90 x 60mm  
Weight: 420gr