

Readers - Proximity, keypad, combined

NANO - mini proximity reader



- Multicolour LED
- Audible feedback
- Temp. -30°C to 60°C
- Power 12Vdc
- NANOPB - black
- NANOPW - white
- 70 x 43 x 23mm

STAR - mullion proximity reader



- Multicolour LED
- Audible feedback
- Temp. -30°C to 60°C
- Power 12Vdc
- STARPB - black
- STARPW - white
- 130 x 41 x 28mm

SOLAR - standard proximity reader



- Multicolour LED
- Audible feedback
- Temp. -30°C to 60°C
- Power 12Vdc
- SOLARPB - black
- SOLARPW - white
- 130 x 90 x 35mm

MOONAR - flush proximity reader



- Multicolour LED
- Audible feedback
- Fits UK back box
- Temp. -30°C to 60°C
- Power 12Vdc
- MOONARWB - black & white covers
- 92 x 85 x 13mm

Readers - Proximity, keypad, combined

SOLARK - proximity card reader and keypad



- Touch sensitive keypad
- Multicolour LED
- Audible feedback
- Temp. -30°C to 60°C
- Power 12Vdc
- SOLARKPB - black
- SOLARKPW - white
- 130 x 90 x 35mm

KCPROXWLC - proximity card reader and keypad



- Vandal resistant housing
- Backlit keys
- Multicolour LED
- Audible feedback
- Temp. -30°C to 60°C
- Power 12Vdc
- 190 x 43 x 27mm

DGLIWLC - stainless steel proximity reader



- Vandal resistant housing
- Multicolour LED
- Audible feedback
- Temp. -30°C to 60°C
- Power 12Vdc
- 140 x 35 x 22mm DGLIFWLC
- 97 x 76 x 20mm DGLIWLC

GALEO/W - 26-bit Wiegand keypad



- Heavy-duty ZAMAK cast alloy
- Soft blue back-lighting
- Audible feedback
- Temp. -30°C to 60°C
- Power 12Vdc
- 110 x 75 x 15mm

Readers - Proximity, keypad, combined

DTRR1434 - long range reader



- Wiegand 26 bits
- Adjustable read range up to 15m
- Built-in antenna
- Temp. -30°C to 60°C
- Power 12 to 30Vdc
- 90 x 60 x 22mm

SOLARM - standard MIFARE reader



- Wiegand 26, 30 or 44 bits
- Multicolour LED
- Audible feedback
- Temp. -30°C to 60°C
- Power 12Vdc
- SOLARMB - black
- SOLARMW - white
- 90 x 130 x 35mm

STAR1M - million MIFARE reader



- Wiegand 26, 30 or 44 bits
- Multicolour LED
- Audible feedback
- Temp. -20°C to 70°C
- Power 12Vdc
- 130 x 41 x 28mm

DGLIMWLC - stainless steel MIFARE reader



- Wiegand 26, 30 or 44 bits
- Multicolour LED
- Audible feedback
- Temp. -30°C to 60°C
- Power 12Vdc
- 97 x 76 x 20mm